



REAR DOOR VAN



- easy installation, stores vertically inside doorway.
- mounts to floor of van inside doorway.
- easily operated by one person.
- three sections, manually operated with spring assist.
- durable welded fabrication.
- anti-slip, high traction surface.

 **Prairie View Industries, Inc.**

prairie view industries, inc. | ramp division | p.o. box 575 | fairbury, ne 68352-0575
phone 800-554-7267 | fax 402-729-4058 | email info@pviramps.com | www.pviramps.com



Prairie view industries, inc.
RAMPS

access ramps

REAR DOOR VAN



FEATURES

- easy installation, stores vertically inside doorway.
- mounts to floor of van inside doorway.
- easily operated by one person.
- three sections, manually operated with spring assist.
- durable welded fabrication.
- anti-slip, high traction surface.
- accommodates wheelchairs and scooters with various wheel configurations.

SPECIFICATIONS

- maximum ramp capacity: 300 lbs. one axle - 600 lbs. two axles.
- minimum requirement for floor to ceiling opening: 7' ramp - 37", 8' ramp - 41".
- minimum inside door opening required is 34" wide.
- conversion kit is required if rear door opening contains a threshold.
- listed by Underwriters Laboratories, Inc.

REAR DOOR VAN				
Item Number	Unfolded Size (feet x inches)	Folded Height (inches)	Weight (lbs.)	Capacity* (lbs.)
VAN727	7' x 27"	36	72	600
VAN827	8' x 27"	40	77	600
* Maximum ramp capacity: 300 lbs. one axle - 600 lbs. two axles.				

Item #:

Model #:

Project #:

Quantity #: