



5110 Atlantic Ave. Raleigh, NC 27616
(855) 996-2100 | AmeriGlide.com

- Purchase Order
- Request for Quote

1. GENERAL INFORMATION

1.1 Dealer Information

Dealer Name
Date (MM/DD/YY)
Address
City
Province/State
Postal Code
Email

1.3 Project

Purchase Order#
Contact
Phone
Ship To
City
Province/State
Postal Code

1.2 Shipping Information

Contact
Phone
Address
City
Province/State
Postal Code/ZIP

1.4 Type of Delivery

Pick-up at Terminal Onsite Forklift
 Loading Dock Flatbed and Forklift
 Liftgate - Ground Delivery

2. PLATFORM CONFIGURATION



STANDARD INCLUSIONS

Each Nano VPL Kit includes the following:

Model:	NANO	Safety Features:	Obstruction sensor underpan limit switches emergency stop emergency lowering slip-resistant floor key lock controls brass safety nut
Dimension:	36W x 54"D x 42" H		
Lifting height:	64"		
Tower height:	92"		
Capacity:	800 lbs		
Speed:	12 fpm		
Color:	Atlas Gray (RAL 7047)	Installation kit:	conductors wiring quick connectors hardware shims touch up paint
Motor:	1 hp, 24VDC motor		
Power supply:	120v/ 20A (2 x 12v gel batteries)		

Safety Standards:

- ASME A18.1
- CSA B44.1 / ASME 17.5-elevator and escalator electrical equipment.
- ICC A117.1 accessible and usable buildings and facilities (section 410)
- Electrical number QAI: E10695

Shipping Details:

Dimensions - 1 Pallet:	98" x 48" x 30"
Weight:	910 lbs

NANO

VERTICAL PLATFORM LIFT

2. PLATFORM CONFIGURATION CONTINUED

2.2 Dimensions

- 34" X 54" (864 mm X 1372 mm)* ***UPCHARGE**
- 34" X 60" (864 mm X 1524mm)* ***UPCHARGE**
- 36" X 54" (915 mm X 1372 mm)
- 36" X 60" (915 mm X 1524 mm)* ***UPCHARGE**

CUSTOM SIZE


CUSTOM SIZE IN INCHES: ____ WIDTH X ____ LENGTH
*** CHOOSE BETWEEN 30" to 44" WIDTH X 46" to 66" LENGTH ***

2.3 Application


- RESIDENTIAL
- COMMERCIAL

2.4 Cab Configuration (Check One)

Tower on LEFT



90°



180°

Tower on RIGHT



90°




180°

3. PLATFORM CONFIGURATION


3.1 Call Station Options (Please select your configuration)

- CALL STATIONS (FLUSH MOUNTED, SURFACE MOUNTED, CALL POST, TOP GATE FRAME MOUNTED)




FLUSH MOUNTED

BOTTOM TOP




SURFACE MOUNTED

BOTTOM TOP



CALL POST

BOTTOM TOP



TOP GATE FRAME MOUNTED

TOP ONLY

4. GATES AND DOORS

4.1 Lower Landing Entrance (Interlock Included)

4.1.1 Platform Gates

CHOOSE AN ORIENTATION:

* WHEN FACING THE GATE/DOOR FROM OUTSIDE OF THE PLATFORM *

LEFT RIGHT

- 34" OR 36" WIDTH X 42" HEIGHT
- 32", 38", 40", 42" WIDTH X 42" HEIGHT

ADDITIONAL OPTIONS

- OPTIONAL LEXAN GATE UPGRADE
- INTERLOCK ONLY

4.1.2 Doors

- 36" WOOD INTERIOR
- 36" FIRE RATED
- 36" EXTERIOR
- 36" POLYCARBONATE
- 38-42" WOOD INTERIOR
- 38-42" FIRE RATED
- 38-42" EXTERIOR
- 38-42" POLYCARBONATE

4.2 Upper Landing Entrance (Interlock Included)

4.2.1 Top Gates

CHOOSE AN ORIENTATION:

* WHEN FACING THE GATE/DOOR FROM OUTSIDE OF THE PLATFORM *

LEFT RIGHT

- 34" OR 36" WIDTH X 42" HEIGHT
- 32", 38", 40", 42" WIDTH X 42" HEIGHT

ADDITIONAL OPTIONS

- OPTIONAL LEXAN GATE UPGRADE
- INTERLOCK ONLY

4.2.2 Doors

- 36" WOOD INTERIOR
- 36" FIRE RATED
- 36" EXTERIOR
- 36" POLYCARBONATE
- 38-42" WOOD INTERIOR
- 38-42" FIRE RATED
- 38-42" EXTERIOR
- 38-42" POLYCARBONATE

5. AUTOMATIC GATE AND DOOR OPENERS

	QUANTITY	TOTAL
<input type="radio"/> DOOR CLOSER (REQUIRED IF NO DOOR OPERATOR INSTALLED)		
<input type="radio"/> AUTOMATIC GATE OPERATOR (RESIDENTIAL ONLY)		
<input type="radio"/> AUTOMATIC DOOR OPENER (RESIDENTIAL)		
<input type="radio"/> AUTOMATIC DOOR OPENER (COMMERCIAL)		
<input type="radio"/> WIRELESS REMOTE (2X)		

6. ADDITIONAL OPTIONS

<input type="radio"/> GRAB RAIL (INCLUDED IN COMMERCIAL KIT)		
<input type="radio"/> ANTI-CORROSION KIT (FOR INSTALLATIONS NEAR POOLS, WATER)		
<input type="radio"/> FOLDING SEAT + HARDWARE (INSTALLATION NOT INCLUDED)		
<input type="radio"/> HANDS-FREE PHONE		
<input type="radio"/> STATIONARY RAMP 40" x 36" x 3"		
<input type="radio"/> TOUCH-UP PAINT	QUANTITY	TOTAL

